



CHEVRON GREY

Chevron boards are partially hand-made, giving a unique appearance to every board. Therefore, the tolerance of bevel precision has an allowance of 3 mm for a maximum of three lamellas in a row between a left & right board. Chevron Grey is a warm brownish grey floor with occasional knots, cracks and fillings. This product requires an, after installation, maintenance treatment using Kährs Satin Oil Matt.

Left version

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151XADEKWKKW18L	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Oil	Design	Pattern	Minimum Mean Density kg/m³		>500 kg/m³
Refining Treatment	Brushed, microbevelled 4-sided	Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	1848 x 305 x 15 mm	Range	Kährs ID	Formaldehyde Emission	EN717-1	E1
Weight per Package	20,01 kg	Collection	Chevron Collection	Content PCP	CEN/TR14823	≤ 5 x 10 ⁻⁶ n
Area per Package	2,04 m²	Natural/Stained	Stained	Breaking Strength N/mm²	EN1533	NPD
Area Per Board	0,51 m²	Brinell Value	3,7	Thermal Conductivity	EN12664	0,14 W/mK
		Joint	Tongue & Groove	Thermal Resistance R-Value		.11 (m2K/W)
		Floor heating	Yes	Biological Durability	EN350-2	Class 1
		Wear-layer material	Hardwood	CARB2		Compliant
		Core material	Poplar			
		Backside material	Oak			
		Thickness	15 mm			
		Installation method	Glue-down			
		EAN Code	7393969041935			
		Surface Colour	Grey			

DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes medium sound and black knots. Knots may vary in size and numbers.

COLOUR CHANGE

Stained product - noticeable color change over time.

CERTIFICATE

