




# ASPELAND

Wear and tear with light colors from bread and flour. Aspeland is an extremely rustic board with knots and cracks giving it an old, restored look.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
<b>Article Number</b>	151NDSEK01KW240	<b>Wood Species</b>	Oak	<b>Moisture content</b>	EN13183	7%±2%
<b>Surface Treatment</b>	Oil	<b>Design</b>	1-strip	<b>Minimum Mean Density kg/m³</b>		>500 kg/m³
<b>Refining Treatment</b>	Bevelled 4-sided, brushed, handscraped, saw marks	<b>Grading</b>	Expressive	<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Dimensions</b>	2420 x 187 x 15 mm	<b>Range</b>	Kährs Supreme	<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Weight per Package</b>	22 kg	<b>Collection</b>	Småland Collection	<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Area per Package</b>	2.72 m²	<b>Natural/Stained</b>	Stained	<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Area Per Board</b>	0.453 m²	<b>Brinell Value</b>	3, 7	<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
		<b>Joint</b>	Woodloc® 5S	<b>Thermal Resistance R-Value</b>		.11 (m2KW)
		<b>Floor heating</b>	Yes	<b>Biological Durability</b>	EN350-2	Class 1
		<b>Wear-layer material</b>	Hardwood	<b>CARB2</b>		Compliant
		<b>Core material</b>	Pine/Spruce lamella			
		<b>Backside material</b>	Veneer			
		<b>Thickness</b>	15 mm			
		<b>Installation method</b>	Floating, glue-down			
		<b>EAN Code</b>	7393969039024			
		<b>Surface Colour</b>	Flour white			
<b>DETAIL DESCRIPTION</b>		<b>CERTIFICATE</b>				
<p>All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.</p>						
<b>COLOUR CHANGE</b>						
<p>Stained product - noticable color change over time.</p>						