



VEDBO

Natural color with enhanced contrast and warmth, golden tones from honey and ripe rye during harvest time. The three dimensional structure enhances the knots, giving the floor a worn look and feel.

PRODUCT DESCRIPTION

Article Number	151NCSEK01KW240
Surface Treatment	Oil
Refining Treatment	Bevelled 4-sided, brushed, handscraped
Dimensions	2420 x 187 x 15 mm
Weight per Package	22 kg
Area per Package	2.72 m ²
Area Per Board	0.453 m ²

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Some muting of colour variation to medium, straw brown.

FACTS

Wood Species	Oak
Design	1-strip
Grading	Dynamic
Range	Kährs Supreme
Collection	Småland Collection
Natural/Stained	Natural
Brinell Value	3, 7
Joint	Woodloc® 5S
Floor heating	Yes
Wear-layer material	Hardwood
Core material	Pine/Spruce lamella
Backside material	Veneer
Thickness	15 mm
Installation method	Floating, glue-down
EAN Code	7393969038966
Surface Colour	Warm natural

CERTIFICATE



TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10 ⁻⁶ n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m ² K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant