



WALNUT HARTFORD

The colour variations found in this dark, 3-strip walnut floor from the American Naturals Collection range from blanché wheat to espresso brown. The silk lacquer finish gives the floor a polished appearance and brings out the natural character of the timber. The even finish protects the wood from daily wear, without adding artificial shine.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	153N29VA50KW 0	Wood Species	Walnut	Moisture content	EN13183	7%±2%
Surface treatment	Silk lacquer	Board	3-strip	Minimum Mean Density kg/m ³		>500 kg/m ³
Dimensions	2423 x 200 x 15 mm	Grading	Variation (Town)	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	23 kg	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Area per Package	2.91 m ²	Collection	American Naturals Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area Per Board	0.485 m ²	Resandable	2-3 times	Breaking Strength N/mm ²	EN1533	NPD
DETAIL DESCRIPTION		Natural/Stained	Natural	Thermal Conductivity	EN12664	0,14 W/mK
Natural colour variations. Also sapwood and small knots.		Brinell Value	3, 4	Thermal Resistance R-Value		.11 (m2K/W)
COLOUR CHANGE		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Changes to golden brown.		Floor heating	Yes	CARB2		Compliant
		Warranty	30 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce lamella			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969018920			

CERTIFICATES

