



## EUROPEAN MAPLE GOTHA

The colour palette found in this 3-strip European maple floor from the Tres Collection is light and bright, ranging from pure cream to golden amber hues. A fine, brown grain and a light scattering of knots bring the wood to life. The silk lacquer finish gives the floor a polished appearance and brings out the natural character of the timber. The even finish protects the wood from daily wear, without adding artificial shine.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	133N18EL50KW0	Wood Species	European maple	Moisture content	EN13183	7%±2%
Surface treatment	Silk lacquer	Board	3-strip	Minimum Mean Density kg/m <sup>3</sup>		>500 kg/m <sup>3</sup>
Dimensions	2423 x 200 x 13 mm	Grading	Variation (Town)	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	24.5 kg	Range	Kährs Avanti	Formaldehyde Emission	EN717-1	E1
Area per Package	3.40 m <sup>2</sup>	Collection	Tres Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area Per Board	0.485 m <sup>2</sup>	Resandable	2-3 times	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
<b>DETAIL DESCRIPTION</b>		Natural/Stained	Natural	Thermal Conductivity	EN12664	0,14 W/mK
		Brinell Value	3,0	Thermal Resistance R-Value		.51 (m <sup>2</sup> K/W)
<b>COLOUR CHANGE</b>		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
		Floor heating	No	<b>CARB2</b>		Compliant
Changes from cream white to golden cream.		Warranty	20 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	2,6 mm			
		Core material	Pine/Spruce lamella			
		Thickness	13 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969034906			

### CERTIFICATES

