



OAK LECCO

Warm brown tones blend with caraway seed hues in this three-strip oak floor from the Tres Collection. The planks have been specially selected with very few knots for a calm and even appearance.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	133NABEK50KW0	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Silk lacquer	Board	3-strip	Minimum Mean Density kg/m ³		>500 kg/m ³
Dimensions	2423 x 200 x 13 mm	Range	Kährs Avanti	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	24.5 kg	Collection	Tres Collection	Formaldehyde Emission	EN717-1	E1
Status in Movex	20	Resandable	2-3 times	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	3.40 m ²	Natural/Stained	Natural	Breaking Strength N/mm ²	EN1533	NPD
Area Per Board	0.485 m ²	Brinell Value	3, 7	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Joint	Woodloc® 5S	Thermal Resistance R-Value		.51 (m2K/W)
Naturally occurring wood colour variations allowed, from light to dark brown. Will include sapwood. The product includes medium sound and black knots. Knots may vary in size and numbers.		Floor heating	Yes	Biological Durability	EN350-2	Class 1
COLOUR CHANGE		Warranty	20 years	CARB2		Compliant
Some muting of colour variation to medium, straw brown.		Wear-layer material	Hardwood			
		Wear-layer thickness	2, 6 mm			
		Core material	Pine/Spruce lamella			
		Thickness	13 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969034166			

CERTIFICATES

