



OAK DUBLIN

Only our finest oak is selected for this exclusive 1-strip/plank product. The natural wood characteristics are enhanced by brushing and micro bevel.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151N4AEK09KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Matt lacquer	Design	1-strip	Minimum Mean Density kg/m ³		>500 kg/m ³
Refining Treatment	Microbevelled 4-sided, brushed	Grading	Calm (City)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2420 x 187 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	22 kg	Collection	Capital Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.72 m ²	Natural/Stained	Natural	Breaking Strength N/mm ²	EN1533	NPD
Area Per Board	0.453 m ²	Brinell Value	3, 7	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Joint	Woodloc® 5S	Thermal Resistance R-Value		.11 (m2KW)
Even colour with minor variations. Small sized knots in limited numbers allowed.		Floor heating	Yes	Biological Durability	EN350-2	Class 1
COLOUR CHANGE		Wear-layer material	Hardwood	CARB2		Compliant
Some muting of colour variation to medium, straw brown.		Core material	Pine/Spruce lamella			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969037532			

CERTIFICATE

