



# DUSSATO

Dussato is an extremely rustic 2-strip board with knots and cracks which gives it a very old look. Smoked and white oiled surface.

## PRODUCT DESCRIPTION

<b>Article Number</b>	152XDDEKFHKW190
<b>Surface Treatment</b>	Oil
<b>Refining Treatment</b>	Bevelled 2-sided, brushed, light smoked, handscraped
<b>Dimensions</b>	1900 x 190 x 15 mm
<b>Weight per Package</b>	19 kg
<b>Area per Package</b>	2.17 m <sup>2</sup>
<b>Area Per Board</b>	0.361 m <sup>2</sup>

## DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

## COLOUR CHANGE

Stained product - noticeable color change over time.

## FACTS

<b>Wood Species</b>	Oak
<b>Design</b>	2-strip
<b>Grading</b>	Expressive
<b>Range</b>	Kährs Supreme
<b>Collection</b>	Da Capo Collection
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3, 7
<b>Joint</b>	Woodloc®
<b>Floor heating</b>	Yes
<b>Wear-layer material</b>	Hardwood
<b>Core material</b>	Pine/Spruce lamella
<b>Backside material</b>	Veneer
<b>Thickness</b>	15 mm
<b>Installation method</b>	Floating, glue-down
<b>EAN Code</b>	7393969036849
<b>Surface Colour</b>	White

## CERTIFICATE



## TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>		>500 kg/m <sup>3</sup>
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.11 (m2KW)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant