



OAK ULF

Oak Ulf is a true rustic product where the surface is handcrafted and deeply brushed to enhance the beauty and specific characteristics of each and every board. Stained to a warm dark grey that gives it a rich colour tone. Nature oil finished.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151N7BEKFBKW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Oil	Design	1-strip	Minimum Mean Density kg/m³		>500 kg/m³
Refining Treatment	Bevelled 4-sided, handscraped, brushed	Grading	Dynamic	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2420 x 187 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	22 kg	Collection	Founders Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.72 m²	Natural/Stained	Stained	Breaking Strength N/mm²	EN1533	NPD
Area Per Board	0.453 m²	Brinell Value	3, 7	Thermal Conductivity	EN12664	0,14 W/mK
		Joint	Woodloc® 5S	Thermal Resistance R-Value		.11 (m2K/W)
		Floor heating	Yes	Biological Durability	EN350-2	Class 1
		Wear-layer material	Hardwood	CARB2		Compliant
		Core material	Pine/Spruce lamella			
		Thickness	15 mm			
		Installation method	Glue-down, floating			
		EAN Code	7393969036030			

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Stained product - noticeable color change over time.

CERTIFICATE

