



Kährs
QUALITY IN WOOD SINCE 1857

KILESAND

White nuances from bread and flour creates contrast that accentuates the natural grain of the wood.

PRODUCT DESCRIPTION

Article Number	153N66EK05KW240
Surface Treatment	Oil
Refining Treatment	Bevelled 4-sided, handscraped, brushed, saw marks
Dimensions	2419 x 196 x 15 mm
Weight per Package	22,4 kg
Area per Package	2.84 m ²
Area Per Board	0,474 m ²

DETAIL DESCRIPTION

Contains knots and all natural colour variations.

COLOUR CHANGE

The colour matures over time

FACTS

Wood Species	Oak
Design	3-strip
Grading	Dynamic
Range	Kährs Original
Collection	Göteborg Collection
Natural/Stained	Stained
Brinell Value	3,7
Joint	Woodloc® 5S
Floor heating	Yes
Wear-layer material	Hardwood
Core material	Pine/Spruce/Alder
Backside material	Spruce
Thickness	15 mm
Installation method	Floating, glue-down
EAN Code	7393969042819
Surface Colour	White

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2KW)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

CERTIFICATE

