



## OAK GATE

Oak Gate is a clean oak floor, which has been colour enhanced through smoking. The colour is a warm brownish oak colour which is strengthened even further by the length of the boards.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	37101REK09KW180	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Matt lacquer	Design	1-strip	Minimum Mean Density kg/m³		>800 kg/m³
Refining Treatment	Microbevelled 4-sided, brushed, light smoked	Grading	Calm (City)	Reaction To Fire	EN13501-1	Cfl-s1
Dimensions	1810 x 150 x 7 mm	Range	Kährs Linnea	Formaldehyde Emission	EN717-1	E1
Weight per Package	20 kg	Collection	Habitat Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	3.26 m²	Natural/Stained	Natural	Breaking Strength N/mm²	EN1533	NPD
Area Per Board	0.272 m²	Brinell Value	5 - 6	Thermal Conductivity	EN12664	0,22 W/mK
DETAIL DESCRIPTION		Joint	Woodloc®	Thermal Resistance R-Value		.31 (m2K/W)
		Floor heating	Yes	Biological Durability	EN350-2	Class 1
		Wear-layer material	Hardwood	CARB2		
		Core material	HDF	Compliant		
		Thickness	7 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969106801			

### COLOUR CHANGE

Stained product - noticable color change over time.

### CERTIFICATE

