



ALLOY

Alight gray with earth tones that works well as a base for a variety of interior styles. The sap wood elements breathe life and variation into the surface.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	153N0BEKD1KW0	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Matt lacquer	Design	3-strip	Minimum Mean Density kg/m³		>500 kg/m³
Refining Treatment	Brushed	Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2423 x 200 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	23 kg	Collection	Harmony Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.91 m²	Natural/Stained	Stained	Breaking Strength N/mm²	EN1533	NPD
Area Per Board	0.485 m²	Brinell Value	3, 7	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Joint	Woodloc® 5S	Thermal Resistance R-Value		.11 (m2K/W)
		Floor heating	Yes	Biological Durability	EN350-2	Class 1
		Wear-layer material	Hardwood	CARB2		
		Core material	Pine/Spruce lamella	Compliant		
		Backside material	Spruce			
COLOUR CHANGE		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969041751			
		Surface Colour	Grey			

CERTIFICATE

