



OAK BREEZE

The sandy blonde hues found in this 2-strip hard oak floor from the Lodge Collection create a calm and even expression, suitable for a range of interiors. The silk lacquer finish gives the floor a polished appearance bringing out the natural character of the timber. The even finish protects the wood from daily wear, without adding artificial shine.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	372034EK50KW0	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Silk lacquer	Board	2-strip	Minimum Mean Density kg/m ³		>800 kg/m ³
Dimensions	1225 x 193 x 7 mm	Grading	Calm (City)	Reaction To Fire	EN13501-1	Cfl-s1
Weight per Package	20 kg	Range	Kährs Linnea	Formaldehyde Emission	EN717-1	E1
Area per Package	2.84 m ²	Collection	Lodge Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area Per Board	0.237 m ²	Resandable	Not resandable	Breaking Strength N/mm ²	EN1533	NPD
DETAIL DESCRIPTION		Natural/Stained	Natural	Thermal Conductivity	EN12664	0,22 W/mK
Even colour with minor variations. Small sized knots in limited numbers allowed.		Brinell Value	5 - 6	Thermal Resistance R-Value		.31 (m ² K/W)
COLOUR CHANGE		Joint	Woodloc®	Biological Durability	EN350-2	Class 1
Some muting of colour variation to medium, straw brown.		Floor heating	Yes	CARB2		Compliant
		Warranty	12 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	0,6 mm			
		Core material	HDF			
		Thickness	7 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969104029			

CERTIFICATES

