

## OAK DAWN

This 3-strip oak floor from the Lumen Collection features warm, washed undertones, with a lighter and calmer expression than most conventional natural oak floors. Each board is carefully brushed to perfection, bringing out the faintly burnished nuances in the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	153N3BEK04KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Ultra matt lacquer	Design	3-strip	Minimun Mean Density kg/m³		>500 kg/m³
Refining Treatment	Brushed	Grading	Variation (Town)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2423 x 200 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	23 kg	Collection	Lumen Collection	Content PCP	CEN/TR14823	≤5 x 10-6n
Area per Package	2.91 m²	Natural/Stained	Natural	Breaking Strength Wmm²	EN1533	NPD
Area Per Board	0.485 m²	Brinell Value	3, 7	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Joint	Woodloc® 5S	Thermal Resistance R-Value		.11 (m2K/W)
		Roor heating	Yes	Biological Durability	EN350-2	Class 1
Even colour with minor variations. Small sized knots in limited numbers allowed.		Wear-layer material	Hardwood	CARB2		Compliant
		Core material	Pine/Spruce/Ader			
COLOUR CHANGE		Backside material	Spruce			
Some muting of colour variation to medium, straw brown.		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969044240			

CERTIFICATE

