OAK SHORE

The mineral grey notes in this single-strip oak floor from the Lux Collection are awash with subtle earth tones, eloquently complemented by the ultra-matt lacquer finish. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DESCRIPTION

Article Number	151N8AEKE4KW240
Surface treatment	Ultra matt lacquer
Design features	Microbevelled 4-sided, brushed
Dimensions	2420 x 187 x 15 mm
Weight per Package	22 kg
Area per Package	2.72 m²
Area Per Board	0.453 m²

DETAIL DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Stained product - noticable color change over time

FACTS

Wood Species	Oak
Board	1-strip
Grading	Lively (Country)
Range	Kährs Original
Collection	Lux Collection
Resandable	2-3 times
Natural/Stained	Stained
Brinell Value	3, 7
Joint	Woodloc® 5S
Floor heating	Yes
Warranty	30 years
Wear-layer material	Hardwood
Wear-layer thickness	3, 5 mm
Core material	Pine/Spruce/Alder
Backside material	Spruce
Thickness	15 mm
Installation method	Floating, glue-down
EAN Code	7393969044219
Surface Colour	Grey

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m³		>500 kg/m³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

CERTIFICATES

CE