



OAK SUN

This single-strip oak floor from the Lux Collection features warm, washed undertones, with a lighter and calmer expression than most conventional natural oak floors. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection, bringing out the faintly burnished nuances in the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151N8AEK04KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Ultra matt lacquer	Design	1-strip	Minimum Mean Density kg/m ³		>500 kg/m ³
Refining Treatment	Microbevelled 4-sided, brushed	Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2420 x 187 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	22 kg	Collection	Lux Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.72 m ²	Natural/Stained	Natural	Breaking Strength N/mm ²	EN1533	NPD
Area Per Board	0.453 m ²	Brinell Value	3, 7	Thermal Conductivity	EN12664	0,14 W/mK
		Joint	Woodloc® 5S	Thermal Resistance R-Value		.11 (m2KW)
		Floor heating	Yes	Biological Durability	EN350-2	Class 1
		Wear-layer material	Hardwood	CARB2		Compliant
		Core material	Pine/Spruce/Alder			
		Backside material	Spruce			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969044172			

DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots and fillings. Knots and fillings may vary in size and numbers.

COLOUR CHANGE

Some muting of colour variation to medium, straw brown.

CERTIFICATE

