



OAK NOUVEAU TAWNY

Deep and dark tones with a warm glow underneath creates a robust and full-bodied atmosphere.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151N8AEKA1KW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Matt lacquer	Design	1-strip	Minimum Mean Density kg/m³		>500 kg/m³
Refining Treatment	Brushed, microbevelled 4-sided	Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2420 x 187 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	22 kg	Collection	Classic Nouveau Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.72 m²	Natural/Stained	Stained	Breaking Strength N/mm²	EN1533	NPD
Area Per Board	0.453 m²	Brinell Value	3, 7	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Joint	Woodloc® 5S	Thermal Resistance R-Value		.11 (m2K/W)
		Floor heating	Yes	Biological Durability	EN350-2	Class 1
		Wear-layer material	Hardwood	CARB2		Compliant
		Core material	Pine/Spruce lamella			
		Backside material	Spruce			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
COLOUR CHANGE		EAN Code	7393969041713			
		Surface Colour	Dark brown			

CERTIFICATE

