



## OAK SAFARI

Intense brown nuances cover a honey-colour base, while well-defined knots and cracks give this single-strip oak floor from the the Rugged Collection its unmistakable character. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Light and dark contrasts in the wood are punctuated with occasional saw marks, giving the floor its restored appearance.

### PRODUCT DESCRIPTION

<b>Article Number</b>	101P8QEKFKKW180
<b>Surface treatment</b>	Oil
<b>Design features</b>	Microbevelled 4-sided, smoked, saw marks
<b>Dimensions</b>	1830 x 125 x 10 mm
<b>Weight per Package</b>	16, 75 kg
<b>Area per Package</b>	1.83 m <sup>2</sup>
<b>Area Per Board</b>	0.228 m <sup>2</sup>

### DETAIL DESCRIPTION

### COLOUR CHANGE

Smoked product - little colour change.

### FACTS

<b>Wood Species</b>	Oak
<b>Board</b>	1-strip
<b>Grading</b>	Dynamic
<b>Range</b>	Kährs Spirit
<b>Collection</b>	Rugged Collection
<b>Resandable</b>	1 time
<b>Natural/Stained</b>	Natural
<b>Brinell Value</b>	3, 7
<b>Joint</b>	Woodloc®
<b>Floor heating</b>	Yes
<b>Warranty</b>	20 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	1, 9 mm
<b>Core material</b>	HDF
<b>Thickness</b>	10 mm
<b>Installation method</b>	Floating, glue-down
<b>EAN Code</b>	7393969043809
<b>Surface Colour</b>	Brown FK

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>		>800 kg/m <sup>3</sup>
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.07 (m <sup>2</sup> K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

### CERTIFICATES

