

## OAK TRENCH

A misty-grey stain gives this single-strip oak floor from the Rugged Collection a calm and pared-back feel, while knots and cracks create a rustic expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	101P8HEKFMKW180	Wood Species	Oak	Moisture content	EN13183	7%±2%
		Board	1-strip	Minimun Mean Density kg/m³		>800 kg/m <sup>3</sup>
Surface treatment	Oil	Grading	Dynamic	Reaction To Fire	EN13501-1	Dfl-s1
Design features	Mcrobevelled 4-sided, brushed, handscraped	Range	Kährs Spirit	Formaldehyde Emission	EN717-1	E1
		Collection	Rugged Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Dimensions	1830 x 125 x 10 mm	Resandable	1 time	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Weight per Package	16, 75 kg	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Area per Package	1.83 m <sup>2</sup>	Brinell Value	3, 7	Thermal Resistance R-Value		.07 (m2K/W)
		Joint	Woodloc®	Biological Durability	EN350-2	Class 1
Area Per	0.228 m²	Roor heating	Yes	CARB2		Compliant
Board		Warranty	20 years			
DETAIL DESCRIPTION		Wear-layer material	Hardwood			
Al naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.		Wear-layer thickness	1, 9 mm			
		Core material	HDF			
		Thickness	10 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969043793			
COLOUR CHANGE		Surface Colour	Grey FM			

Stained product - noticable color change over time.

## CERTIFICATES