



OAK BRIGHTON

Oak Brighton (white pigmented, matt lacquer finish) is an exclusive 1-strip floor (board). This means that the visible part of each board (wearing surface) is taken from one piece of wood. Nature's own design with knots and a lively structure.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151L87EK0VKW220	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Matt lacquer	Design	1-strip	Minimum Mean Density kg/m ³		>500 kg/m ³
Dimensions	2266 x 187 x 15 mm	Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	21 kg	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Area per Package	2,54 m ²	Collection	Sand Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area Per Board	0,423 m ²	Natural/Stained	Stained	Breaking Strength N/mm ²	EN1533	NPD
DETAIL DESCRIPTION		Brinell Value	3, 7	Thermal Conductivity	EN12664	0,14 W/mK
Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers.		Joint	Woodloc®5S	Thermal Resistance R-Value		.11 (m2K/W)
COLOUR CHANGE		Floor heating	Yes	Biological Durability	EN350-2	Class 1
Stained product - noticable color change over time.		Wear-layer material	Hardwood	CARB2		Compliant
		Core material	Pine/Spruce lamella			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969041164			
		Surface Colour	White			

CERTIFICATE

