



OAK VISTA

This misty white stained, single-strip oak floor from the Småland Collection gracefully balances the light and dark contrasts in the wood. Each board is meticulously hand-scraped, which enhances the rustic appearance of the floor. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

| PRODUCT DESCRIPTION | | FACTS | | TECHNICAL PROPERTIES | | |
|---|--|-----------------------------|---------------------|-----------------------------------|-------------|-------------|
| Article Number | 151NCSEK02KW240 | Wood Species | Oak | Moisture content | EN13183 | 7%±2% |
| Surface treatment | Oil | Board | 1-strip | Minimum Mean Density kg/m³ | | >500 kg/m³ |
| Design features | Bevelled 4-sided, brushed, handscraped | Grading | Dynamic | Reaction To Fire | EN13501-1 | Dfl-s1 |
| Dimensions | 2420 x 187 x 15 mm | Range | Kährs Supreme | Formaldehyde Emission | EN717-1 | E1 |
| Weight per Package | 22 kg | Collection | Småland Collection | Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Area per Package | 2.72 m² | Resandable | 2-4 times | Breaking Strength N/mm² | EN1533 | NPD |
| Area Per Board | 0.453 m² | Natural/Stained | Stained | Thermal Conductivity | EN12664 | 0,14 W/mK |
| | | Brinell Value | 3, 7 | Thermal Resistance R-Value | | .11 (m2K/W) |
| | | Joint | Woodloc® 5S | Biological Durability | EN350-2 | Class 1 |
| | | Floor heating | Yes | CARB2 | | Compliant |
| | | Warranty | 30 years | | | |
| | | Wear-layer material | Hardwood | | | |
| | | Wear-layer thickness | 3, 5 mm | | | |
| | | Core material | Pine/Spruce lamella | | | |
| | | Backside material | Veneer | | | |
| | | Thickness | 15 mm | | | |
| | | Installation method | Floating, glue-down | | | |
| | | EAN Code | 7393969038973 | | | |
| | | Surface Colour | Misty white | | | |
| DETAIL DESCRIPTION | | | | | | |
| All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. | | | | | | |
| COLOUR CHANGE | | | | | | |
| Stained product - noticable color change over time. | | | | | | |

CERTIFICATES

