



REEF OAK

Reef oak is a natural one strip design. May contain small knots and mild color variation.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	101P3AEK09KW180	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Matt lacquer	Design	1-strip	Minimum Mean Density kg/m ³		>800 kg/m ³
Refining Treatment	Bevelled 4-sided, brushed	Grading	Variation (Town)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	1830 x 125 x 10 mm	Range	Kährs Spirit	Formaldehyde Emission	EN717-1	E1
Weight per Package	16,75 kg	Collection	Unity Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	1.83 m ²	Natural/Stained	Natural	Breaking Strength N/mm ²	EN1533	NPD
Area Per Board	0,228 m ²	Brinell Value	3,7	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Joint	Woodloc®	Thermal Resistance R-Value		.07 (m2KW)
		Floor heating	Yes	Biological Durability	EN350-2	Class 1
Even colour with minor variations. Small sized knots in limited numbers allowed.		Wear-layer material	Hardwood	CARB2		Compliant
		Core material	HDF			
COLOUR CHANGE		Backside material	Veneer			
		Thickness	10 mm			
Some muting of colour variation to medium, straw brown.		Installation method	Floating, glue-down			
		EAN Code	7393969030601			

CERTIFICATE

